

Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

Supplier: Product Name: MPPL Liquid Maxima Racing Oils Article Number: 95-04904

9266 Abraham Way

Santee, CA 92071

+1 619 449 5000

USA

Applications: Lubricant/Protectant

Emergency Telephone: In USA: CHEMTREC +1 703 527 3887 (24 hours)

Outside USA: +1 619 449 5000

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquid Category 2
Aspiration Hazard Category 1
Skin Irritant Category 2

Skin Sensitizer Category 1B

Specific Target Organ Toxicity – Single

Exposure

Category 3

Toxic to Reproduction Category 2









Signal Word Danger!

Hazard Statements H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment

P241 Use explosion-proof electrical, ventilating and lighting equipment.



Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fume, gas, mist, vapors or spray.

P264 Wash thoroughly after handling

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P333 + P313 If skin irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P308 + P313 IF exposed or concerned: Get medical attention.

P370 + P378 In case of fire: Use carbon dioxide, foam or dry chemical to

extinguish.

Storage P405 Store locked up.

Disposal Dispose of contents and container in accordance with local, regional and national

regulations.

Other Hazards None

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	Content %	CAS Number
Hydrotreated light distillate (Petroleum)	40-60	64742-47-8
Petroleum Distillates	10-20	64742-89-8
Heptane	5-15	142-82-5
Calcium Sulfonate	1-3	Trade Secret

The specific identity and/or exact percentage has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation Immediately remove to fresh air. If breathing is difficult have qualified

personnel administer oxygen. If breathing has stopped, administer artificial

respiration. Get medical attention.

Skin Contact Remove contaminated clothing. Wash skin thoroughly with soap and water. If

irritation or rash develops, get medical attention. Launder clothing before re-

use.

Eye Contact Flush eyes with large quantities of water, holding the eyelids apart. Get

medical attention if irritation develops or persists.



Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

Ingestion Aspiration Hazard. Do not induce vomiting. If conscious, rinse mouth with

> water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration

into the lungs. Get immediate medical attention.

Immediate medical attention is required for ingestion.

Most Important Symptoms

May cause eye irritation. Causes skin irritation. May cause an allergic skin reaction. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Aspiration hazard: Harmful or fatal if swallowed. Suspected of causing reproductive or developmental effects based on animal

Indication of

Immediate Medical Attention Needed

Notes to Physician Treat appropriately.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing

Media

Use carbon dioxide, alcohol foam or dry chemical. Water may be ineffective but can be used to cool exposed containers and structures and disperse

flammable vapors.

Specific Hazards Arising From The

Chemical

This product is highly flammable and forms explosive mixtures with air. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Closed containers may explode if exposed to

extreme heat. Combustion may produce carbon oxides.

Special Protective Equipment And Precautions For Fire-

Fighters

Firefighters should wear full emergency equipment and an approved positive pressure self-contained breathing apparatus. Cool exposed intact

containers with water.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Evacuate spill area and keep unprotected personnel away. Remove all

> sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing. See also: "Personal Protection "section 8.

Environmental Hazards Avoid release into the environment. Report spill as required by local and

federal regulations.

Methods/Materials for

Cleaning up

Contain and collect using inert absorbent materials and place in

appropriate containers for disposal. Use non-sparking tools and equipment. If spill has not ignited, use water spray to disperse the vapors and protect personnel attempting to stop leak. Ensure collected material is handled in

accordance with section 13 "Disposal Considerations".



Version: 1.2

Revision Date: 2024-04-09

7. HANDLING AND STORAGE

Precautions for Safe Handling

Released: 2016-05-05

Avoid contact with the eyes, skin and clothing. Do not breathe vapors or mists. Wear protective clothing and equipment. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep away from heat, sparks, flames and all other sources of ignition. Do not permit smoking in use or storage areas. Store in a cool, dry, well-ventilated area away from heat, direct sunlight and all sources of ignition. Store in accordance with regulations for the storage of flammable liquids. Store away from oxidizers and other incompatible

Conditions for Safe Storage

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits		
Hydrotreated light distillate	5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)		
(Petroleum)	5 mg/m3 TWA OSHA PEL (as oil mist, mineral)		
Petroleum Distillates	5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)		
r ctroicam bistiliates	5 mg/m3 TWA OSHA PEL (as oil mist, mineral)		
Heptane	400 ppm TWA, 500 ppm STEL ACGIH TLV		
rieptune	500 ppm TWA OSHA PEL		
Calcium Sulfonate	None Established		

materials. Protect from physical damage.

Appropriate Engineering Controls Use with adequate local exhaust ventilation to maintain exposures below the occupational exposure limits. Use explosion proof equipment where required.

Personal Protection

Respiratory Protection If the exposure limits are exceeded, an approved organic vapor respirator

appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance

with local regulations and good industrial hygiene practice.

Eye Protection Skin/Body Protection

Wear chemical safety glasses or goggles to prevent eye contact.

Wear protective clothing if needed to avoid skin contact and contamination of personal clothing. Suitable washing should be available in the work area. Contaminated clothing should be removed and laundered before re-use.

Hand Protection Wear impervious gloves to avoid prolonged skin contact.

SAFETY DATA SHEET





MPPL LIQUID

Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid Color Clear

Odor Characteristic odor
Odor Threshold No data available
pH No data available
Freezing Point No data available

Boiling Point 98.2 - 98.4 °C (208.76 – 209.12) (Heptane)

Flash Point -4 °C (24.8 °F) (Heptane)

Evaporation Rate No data available
Flammability (solid, gas) Not applicable
Upper Explosion Limit 6.7% (heptane)
Lower Explosion Limit 1.05% (t heptane)

Vapor Pressure 6.09 kPa @ 25°C (77°F) (Heptane)

Vapor Density (Air=1) No data available

Relative Density 0.69 @ 15°C (59°F) (Heptane)

Solubility In water: 2.4 mg/L @ 25°C (77°F) (Heptane)

Partition Coefficient: n- No data available

octanol/water

Auto Ignition 204°C (399.2°F) (Heptane)

Temperature

Decomposition No data available

Temperature

Volatile Organic No data available

Compounds (VOC)

Viscosity 0.641 mm2/s @ 20° (68°F)

10. STABILITY AND REACTIVITY

Reactivity Not expected to be reactive.

Chemical Stability Stable.

Possibility of Hazardous

Reactions

None known.

Conditions to Avoid Keep away from heat, sparks, flames and all other sources of ignition.

Incompatible Materials
Avoid contact with strong oxidizing agents, halogens, peroxides and

strong reducing agents.



Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

Hazardous Thermal decomposition may produce carbon oxides.

Decomposition Product

11. TOXICOLOGICAL INFORMATION

Potential Health Hazards

Eye Contact: May cause irritation with redness and tearing.

Skin Contact: Causes irritation with redness and drying of the skin. Prolonged contact may cause defatting of the skin and dermatitis. May cause an allergic skin reaction.

Inhalation: Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, giddiness, intoxication, nausea, vomiting, disorientation, stupor and unconscious. Severe exposures may cause pulmonary edema.

Ingestion: Ingestion may cause mucous membrane and gastrointestinal irritation and nervous system depression with symptoms of headache, dizziness, nausea, narcosis and unconsciousness. Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

Chronic Effects of Overexposure: None known.

Sensitization: This product is classified as a skin sensitizer. Calcium Sulfonate is classified as a skin sensitizer based on a read-across study.

Mutagenicity: No data available for mixture. Components are not germ cell mutagens.

Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects. **Carcinogenicity:** None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP, or OSHA.

Acute Toxicity:

Hydrotreated light distillate (Petroleum): Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >4.3 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg

Petroleum Distillates: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 2.18 mg/L, Dermal rabbit LD50 >2000 mg/kg

Heptane: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >29.29 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg

Calcium Sulfonate: No data available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Hydrotreated light distillate (Petroleum): 96 hr LL50 Oncorhynchus mykiss: 2-5 mg/L Petroleum Distillates: 96 hr LL50 Pimephales promelas >100 mg/L, 48 hr EL50 >10000 mg/L Heptane: 96 hr LL50 Oncorhynchus mykiss 5.29 mg/L, 48 hr EC50 daphnia magna 1.5 mg/L, 72 hr EC50 Pseudokirchnerella subcapitata 4.338 mg/L, 21 days NOEC daphnia magna: 0.17 mg/L

This product is toxic to aquatic life with long lasting effects. Releases to the environment should be avoided.



Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

Biodegradation Heptane is readily biodegradable. Petroleum distillates are inherently

biodegradable.

Bioaccumulation Heptane has BCF less than 3. This suggests the bioconcentration in aquatic

organisms is expected to be low.

Mobility in soil Heptane is moderately mobile in soil.

Other adverse effects None known.

13. DISPOSAL CONSIDERATIONS

Disposal Dispose in accordance with all local, state and national regulations.

14. TRANSPORT INFORMATION

	UN	Proper shipping name	Hazard	Packing	Environmental
	Number		Class	Group	Hazard
DOT	UN1268	Petroleum distillates, n.o.s.	3	PGII	Marine
					Pollutant
TDG	UN1268	Petroleum distillates, n.o.s.	3	PGII	No
IMDG	UN1268	Petroleum distillates, n.o.s.	3	PGII	Marine
					Pollutant
IATA	UN1268	Petroleum distillates, n.o.s.	3	PGII	No

Note: This product can be shipped as a limited quantity if the packaging complies.

Note: Inner packages with less than 5 liters of liquid/ 5 kg of solid are exempt from Marine Pollutant per DOT 171.4, IMDG Code 2.10.2.7 and ICAO Special Provision A197.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form

Special precautions: None known.

15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements; however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 Hazard Classification: Acute Health, Chronic Health, Fire Hazard

SAFETY DATA SHEET





MPPL LIQUID

Version: 1.2

Released: 2016-05-05 Revision Date: 2024-04-09

California Proposition 65: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Chemical Inventories

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory

16. OTHER INFORMATION

NFPA Rating (NFPA 704): Health: 2 Fire: 3 Instability: 0 HMIS Rating: Health: 2* Fire: 3 Physical Hazard: 0

*Chronic Health Hazard

Date of Revision: September 11, 2024 Date of Previous Revision: April 9, 2024

Revision History:

5/5/16: New document

11/6/17: Updated emergency telephone #

4/9/2024: Document reviewed

9/11/24: Reviewed all sections and ensured they are up to date

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.