

Released: 2015-07-10

Version: 1.3 Revision Date: 2024-04-09

1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

Supplier:
Maxima Racing Oils
9266 Abraham Way
Santee, CA 92071
USA
+1 619 449 5000

Product Name: Suspension Clean Article Number: 71920

Applications: Suspension Internal Cleaner

Emergency Telephone: In USA: CHEMTREC +1 703 527 3887 (24 hours) Outside USA: +1 619 449 5000

2. HAZARDS IDENTIFICATION

GHS Classification

7(6103015	
Gases Under Pressure	(
Aspiration Toxicity	(
Skin Irritation	(
Toxic to Reproduction	(
Specific Target Organ Toxicity – Single Exposure	(
Specific Target Organ Toxicity - Repeat Exposure	(

GHS Pictogram

Signal Word Hazard Statements AerosolsCategory 1PressureCompressed Gasa ToxicityCategory 1IrritationCategory 2oductionCategory 2ExposureCategory 3ExposureCategory 2



Danger!

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to central nervous system through prolonged or repeated exposure by inhalation.

Precautionary Statements

Prevention P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames or hot surfaces. No smoking.

- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.



Released: 2015-07-10

SUSPENSION CLEAN

Version: 1.3 Revision Date: 2024-04-09

	P260 Do not breathe mist, vapors or spray
	P264 Wash thoroughly after handling.
	P271 Use only outdoors or in a well-ventilated area.
	P280 Wear protective gloves.
Response	P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor. P331 Do NOT induce vomiting.
	P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
	P332 + P313 If skin irritation occurs: Get medical attention.
	P362 + P364 Take off contaminated clothing and wash it before reuse.
	P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for
	breathing.
	P312 Call a POISON CENTER or doctor if you feel unwell.
	P308 + P313 IF exposed or concerned: Get medical attention.
Storage	P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
	P405 Store locked up.
	P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122 F.
Discond	
usposal	P501 Dispose of contents and container in accordance with local and national
	regulations.
her Hazards	None

Other Hazards

None

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	Content %	CAS Number
Hexane	60-100	110-54-3
Carbon Dioxide	1-5	124-38-9

The specific identity and/or exact percentage has been withheld as a trade secret.

4. FIRST-AID MEASURES		
Inhalation	Immediately remove to fresh air. If breathing is difficult have qualified	

Inhalation	Immediately remove to fresh air. If breathing is difficult have qualified
	personnel administer oxygen. If breathing has stopped, administer artificial
	respiration. Get medical attention.
Skin Contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. If
	irritation develops, get medical attention. Launder clothing before re-use.
Eye Contact	Flush eyes with large quantities of water, holding the eyelids apart. Get
	medical attention if irritation develops or persists.
Ingestion	Unlikely route of exposure with an aerosol container. If conscious, rinse
	mouth with water. Do not induce vomiting. Never give anything by mouth to
	an unconscious or convulsing person. If vomiting occurs spontaneously, keep
	head below hips to prevent aspiration into the lungs. Get immediate medical
	attention.



Released: 2015-07-10

Version: 1.3 Revision Date: 2024-04-09

Most Important Symptoms	May cause eye irritation. Causes skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Aspiration hazard: Harmful or fatal if swallowed. Prolonged overexposure may cause nervous system damage. Possible developmental hazard. May adversely affect the developing fetus or cause birth defects based on animal data.
Indication of Immediate Medical Attention Needed Notes to Physician	Get immediate medical attention if swallowed. Treat appropriately

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Use carbon dioxide, foam or dry chemical. Water may be ineffective but can be used to cool exposed containers and structures and disperse flammable vapors.
Specific Hazards	Contents under pressure. Keep away from heat and open flames.
Arising From The	Container may rupture or explode in the heat of a fire. Prolonged exposure
Chemical	to temperatures above 120°F may cause cans to burst. Combustion may produce carbon and nitrogen oxides.
Special Protective	Firefighters should wear full emergency equipment and a NIOSH approved
Equipment And	positive pressure self-contained breathing apparatus. Cool exposed intact
Precautions For Fire-	containers with water. Protect against bursting cans.
Fighters	

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Evacuate spill area and keep unprotected personnel away. Remove all sources of ignition. Ventilate area. Wear appropriate protective clothing. See also: "Personal Protection "section 8.
Environmental Hazards	Avoid release into the environment. Report spill as required by local and federal regulations.
Methods/Materials for Cleaning up	Collect liquid with an absorbent material and place in a container suitable for flammable waste. Ensure collected material is handled in accordance with section 13 "Disposal Considerations".

7. HANDLING AND STORAGE

Precautions for SafeAvoid contact with the eyes, skin and clothing. Do not breathe vapors orHandling:mists. Wear protective clothing and equipment. Use only with adequate
ventilation. Wash thoroughly with soap and water after handling. Keep
away from heat sources. Contents under pressure. Do not smoke during



Released: 2015-07-10

SUSPENSION CLEAN

Version: 1.3 Revision Date: 2024-04-09

	use. Do not expose to temperatures above 120°F. Do not puncture or incinerate containers.
Conditions for Safe	Store in a cool, well-ventilated area at temperatures below 120°F. Do not
Storage	store in direct sunlight. Protect from physical damage.
Aerosol Fire	Level 3 Aerosol (NFPA 30B)
Protection Level	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits	Hexane Carbon Dioxide	50 ppm TWA OSHA PEL 50 ppm TWA, 50 ppm STEL ACGIH TLV 5000 ppm TWA OSHA PEL 5000 ppm TWA, 30,000 STEL ACGIH TLV
Appropriate	General ventilation should be adeq	uate for normal use. If vapor
Engineering Controls	concentrations are excessive, use with adequate local exhaust ventilation to maintain exposures below the occupational exposure limits.	
Personal Protection		
Respiratory	If the exposure limits are exceeded, a NIOSH approved organic vapor	
Protection:		and concentration of the contaminants
	should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice. Wear chemical safety glasses or goggles to prevent eye contact. Protective clothing if needed to avoid skin contact and contamination of	
Eye Protection:		
Skin/Body Protection:		
Skilly Body Protection.	-	should be available in the work area.
		emoved and laundered before re-use.
Hand Protection:	C C	rile or Polyvinyl to avoid skin contact.
	. 0	, ,

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Clear, colorless
Odor	Solvent odor
Odor Threshold	No data available
рН	No data available
Freezing Point	-139°F (-95°C) (hexane)
Boiling Point	63 - 80 °C (145 - 176 °F) (hexane)
Flash Point	-18 °C (-0.40 °F) (hexane)
Evaporation Rate	No data available
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	7.7% (hexane)
Lower Explosion Limit	1.0% (hexane)



Version: 1.3 Revision Date: 2024-04-09

Released: 2015-07-10

Vapor Pressure	6.000 - 7.700 Pa (20 °C / 68 °F)
Vapor Density (Air=1)	>1
Relative Density	0.71
Solubility	Negligible in water
Partition Coefficient: n-	No data available
octanol/water	
Auto Ignition	252 - 258 °C (hexane)
Temperature	
Decomposition	No data available
Temperature	
Volatile Organic	No data available
Compounds (VOC)	
Viscosity	No data available

10. STABILITY AND REACTIVITY

Reactivity Chemical Stability Possibility of Hazardous Reactions	Not expected to be reactive. Stable. None known.
Conditions to Avoid	Keep away from heat, sparks, flames and all other sources of ignition. Dropping containers may cause bursting.
Incompatible Materials	Avoid contact with strong oxidizing agents and acids. May attack some plastics, rubber and coatings.
Hazardous Decomposition Product	Thermal decomposition may produce carbon and nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Potential Health Hazards

Eye Contact: May cause mild irritation with redness and tearing.

Skin Contact: Causes irritation with redness and drying of the skin. Prolonged contact may cause defatting of the skin and dermatitis.

Inhalation: Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, giddiness, intoxication, nausea, vomiting, disorientation, stupor and unconscious.

Ingestion: Ingestion may cause mucous membrane and gastrointestinal irritation and nervous system depression with symptoms of headache, dizziness, nausea, narcosis and unconsciousness. Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal. **Chronic Effects of Overexposure:** Prolonged occupational overexposure may cause effects on damage to the central and peripheral nervous systems, fatigue, loss of appetite, paresthesia in distal



Released: 2015-07-10

Version: 1.3 Revision Date: 2024-04-09

extremities, blurred vision, headache, anorexia, muscular weakness, loss of sensation, and impaired gait.

Sensitization: None of the components have been found to cause sensitization in animals or humans. **Mutagenicity:** This product is not expected to cause mutagenic activity.

Reproductive Toxicity: Prolonged exposure to high concentrations of n-hexane (>1,000 ppm) resulted in decreased sperm count and degenerative changes in the testes of rats but not those of mice. In a reproductive inhalation study, female rats were exposure to up to 5000 ppm for 20 hrs a day during days 6-20 of gestation. Maternal and fetal weights were reduced in the 1000 and 5000 ppm dose groups. A significant increase in reduced ossification of sternebrae 1 -4 in the 5000 ppm fetuses, but this was likely due to the fetal growth retardation. NOEC for maternal toxicity is 200 ppm. The NOAEC for developmental toxicity is 200 ppm.

Carcinogenicity: None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP, or OSHA.

Hexane:	Oral rat LD50 16,000 mg/kg; Inhalation rat LC50 >73.86 mg/L/4 hr;	
	Dermal rabbit LD50 3350 mg/kg	
Carbon Dioxide:	No toxicity data available. Considered a simple asphyxiant.	

12. ECOLOGICAL INFORMATION			
Ecotoxicity			
Heptane:	96 hr LL50 Oncorhynchus mykiss 12.51 mg/L, 48 hr EC50 daphnia magna 21.85 mg/L; 72 hr EC50 Pseudokirchnerella subcapitata 9.285 mg/L		
Carbon Dioxide:	96 hr LC50 Oncorhynchus mykiss 35 mg/L		
Biodegradation Bioaccumulation	Hexane is readily biodegradable. Hexane has BCF of 170. This suggests the bioconcentration in aquatic organisms is expected to be high.		
Mobility in soil Other adverse effects:	Hexane is highly mobile in soil. None known.		

13. DISPOSAL CONSIDERATIONS

Disposal Dispose in accordance with all local, state and federal regulations. Do not puncture or incinerate containers.



Version: 1.3 Revision Date: 2024-04-09

Released: 2015-07-10

14. TRANSPORT INFORMATION

	UN	Proper shipping name	Hazard	Packing	Environmental
	Number		Class	Group	Hazard
DOT	UN1950	Aerosols	2.1		
TDG	UN1950	Aerosols	2.1		
IMDG	UN1950	Aerosols	2.1	LTD QTY	
ΙΑΤΑ	UN1950	Aerosols	2.1		

Note: This product can be shipped as a limited quantity if the packaging complies.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form

Special precautions: None known.

15. REGULATORY INFORMATION

CERCLA: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for hexane (100% maximum) of 5,000 lbs, is 5,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 Hazard Classification: Acute Health, Chronic Health, Fire Hazard, Sudden Release of Pressur EPA SARA 313: This product contains the following chemicals that are regulated under SARA Title III, section 313: None

California Proposition 65: This product contains the following chemicals known to the State of California t cause cancer and reproductive toxicity:

Hexane 60-100 110-54-3

Chemical Inventories

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory



Version: 1.3 Revision Date: 2024-04-09

Instability: 0

Physical Hazard: 0

Released: 2015-07-10

16. OTHER INFORMATION

NFPA Rating (NFPA 704):	Health: 2	Fire: 3
HMIS Rating:	Health: 2*	Fire: 4
*Chronic Health Hazard		

Date of Revision: April 9, 2024 Date of Previous Revision: October 11, 2022 Revision History: 7/10/15: Converted to GHS format. All section revised 11/7/17: Updated emergency telephone # 10/11/22: Updated CA P65 Warning Statement 4/9/2024: Document reviewed

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.